Category:

Item Name: Lube Skid, EC 516010

NSN: 4930-LL-LCC-6182

LIN:

Part Number (Model Number):

Description: The Lube Skid is designed to conduct service

maintenance on construction equipment in the field by dispensing lubricants, fuel, and providing air for tire. Mountable by fork lift or crane on the MK915A3 stake bed truck, utilizing ISO container fittings.

Version: Lube Skid

Dimension: 48"H x 96"W x 158"L

Weight:

Capability: A full Lubrication Service System, that is fully self-contained in a SIXCON Configuration and stackable with other SIXCON's. It operates on the ground, or mounted on a MTVR, or M915A3 (Field Service Body Truck). This system was designed for use by NEMSCOM however, it is fully capable to support a variety of activities and can be integrated with SIXCON Fuel Systems and/or fuel manifold(s)

Electrical Power:

Transportability:

Used By (Service): Navy

Other Characteristics:

- Self-contained, transportable Lubricant Service System for providing bulk volumes of lubricants, dispensing lubricants and fuel as required, and providing air for tire maintenance.
- Able to operate when engine is out of service and Lube Skid can be powered by M914A3 stake bed truck
- Mountable on MTVR or MK915A3
- 50 foot reach for dispensing fuel, POL products, grease, air maintenance, and dispensing/retrieving waste oil
- Able to operate in temperature conditions from -30(°F) to +125(°F)

Support Equipment (Ancillary):

Primary Inventory Control Authority (PICA):

Supportability:

